



TECHNICAL SPECIFICATION

- Mode switch for stereo 2-way or mono 3-way operation
- Low frequency summed (subwoofer) output
- x10 range switch on both channel
- 40Hz high pass (low cut) filter both channel
- Phase reverse switch on all output
- Individual level control on all output
- 24dB/octave Linkwitz-Riley filter (the professional standard)
- Stereo/Mono status LED indicate the selected mode

INPUT

Connector XLR
 Type Electronically balanced/unbalanced, RF filtered
 Impedance Balanced > 50KΩ, unbalanced > 25KΩ
 Max Input Level > +21dBu balanced or unbalanced
 CMRR > 40dBu, typically > 50dB at 1KHz

OUTPUT

Connector XLR
 Type Impedance balanced/unbalanced, RF filtered
 Impedance Balanced 200Ω, unbalanced 100Ω
 Max Output Level .. > +21dBu balanced/unbalanced into 2KΩ or greater
 CMRR > 40dBu, typically > 50dB at 1KHz

SYSTEM PERFORMANCE

Bandwidth 20Hz to 20KHz, +0/-0.5dB
 Frequency Response < 3Hz to > 90KHz, +0/-3dB
 Signal to Noise Ref. +4dBu, 22KHz measurement bandwidth

Stereo Mode
 : Low Output > 94dB
 : High Output > 92dB

Mono Mode
 : Low Output > 94dB
 : Mid Output > 93dB
 : High Output > 92dB

Dynamic Range > 114dB, unweighted, any output
 THD+Noise < 0.004% at +4dBu, 1KHz
 < 0.04% at +20dBu, 1KHz
 Interchannel Crosstalk < -80dB, 20Hz to 20KHz

CROSSOVER FREQUENCY

Stereo Mode
 : Low/High 45Hz to 960Hz or 450Hz to 9.6KHz (x10 Setting)

Mono Mode
 : Low/Mid 45Hz to 960Hz or 450Hz to 9.6KHz (x10 Setting)
 : Mid/High 45Hz to 960Hz or 450Hz to 9.6KHz (x10 Setting)

Filter Type Linkwitz-Riley, 24dB/octave, state-variable

FUNCTION SWITCH

Front Panel
 : Low Cut Activates 40Hz butterworth, 12dB/octave high-pass filter, one switch per channel
 : Phase Invert Inverts the phase at the output, one switch per output

Rear Panel
 : x10 Multiplies crossover frequency range by 10, one switch per channel
 : Mode Selects stereo/mono and 2/3/4-way operation
 : LF Sum Selects normal (stereo) or mono-summed low frequency operation

INDICATOR

Stereo Operation Green LED
 Mono Operation Yellow LED
 Low Cut RED LED per channel
 x10 Green LED per channel
 Phase Invert Red LED per output (2 per channel)

POWER SUPPLY

Operating Voltage 230VAC 50Hz
 Power Consumption 15 Watts
 Main Connection IEC 320 receptacle

PHYSICAL

Dimension [HxWxD] 1.75" x 19" x 6.9" (4.4cm. x 48.3cm. x 17.5 cm.)
 Weight 3.7 lbs. (1.7 Kg.)
 Shipping Weight 5.4 lbs. (2.5 Kg.)

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
 NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897