

PASSIVE PORTABLE

ABS LOUDSPEAKER



TECHNICAL SPECIFICATION

JX-8 / JX-10 / JX-12 / JX-15 : PASSIVE PORTABLE LOUDSPEAKER

	JX-8	JX-10	JX-12	JX-15
Frequency response	60Hz ~ 18KHz	50Hz ~ 18KHz	45Hz ~ 18KHz	40Hz ~ 18KHz
Sensitivity [1w/1m]	92dB	93dB	96dB	98dB
RMS power handling	100W RMS	150W RMS	200W RMS	300W RMS
Voice coil	1.5" KSV	2" KSV	2.5" KSV	3" KSV
Magnet	30 Oz.	40 Oz.	50 Oz.	60 Oz.
Low frequency	8" Woofer	10" Woofer	12" Woofer	15" Woofer
High frequency	1" (25 mm.)	1" (25 mm.)	1.34" (34 mm.)	1.75" (44 mm.)
Nominal impedance	8Ω	8Ω	8Ω	8Ω

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897