

# JX-8A / JX-10AU

ACTIVE PORTABLE LOUDSPEAKER



## ACTIVE PORTABLE ABS LO



**JX-8A**  
8 inch  
WOOFER



**JX-10AU**  
10 inch  
WOOFER



### TECHNICAL SPECIFICATION

JX-8A : ACTIVE PORTABLE LOUDSPEAKER

#### JX-8A

Frequency response .....	60Hz ~ 18KHz
Sensitivity [1w/1m] .....	92dB
Power handling .....	100W
Voice coil .....	1.5" KSV
Magnet .....	30 Oz.
Low frequency .....	8" Woofer
High frequency .....	1" (25 mm.)
Nominal impedance .....	8Ω

#### POWER AMPLIFIER

Rated power .....	100W
AC Main .....	220 VAC, 50 Hz

JX-10AU : ACTIVE PORTABLE LOUDSPEAKER  
with USB SLOT / LCD SCREEN / REMOTE

#### JX-10AU

Frequency response .....	50Hz ~ 18KHz
Sensitivity [1w/1m] .....	93dB
Power handling .....	150W
Voice coil .....	2" KSV
Magnet .....	40 Oz.
Low frequency .....	10" Woofer
High frequency .....	1" (25 mm.)
Nominal impedance .....	8Ω

#### POWER AMPLIFIER & USB SLOT / LCD SCREEN / REMOTE

Rated power .....	150W
AC Main .....	220 VAC, 50 Hz

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด  
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: [nts@nts-solution.com](mailto:nts@nts-solution.com)

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897