



## TECHNICAL SPECIFICATION

- KP-80 : Stereo Mixer 8 Mono Input
- KP-120 : Stereo Mixer 12 Mono Input
- KP-160 : Stereo Mixer 16 Mono Input

- 3 band EQ on all input
- 1 Aux send for external effects and monitoring
- Peak LED on all input
- PAD and PFL switch on all input
- Built in 16 program digital effect
- USB interface for MP3 input and playback with digital display
- Dual 7 band graphic EQ

### MAIN SPECIFICATION :

Channel .....	8 mono input [KP-80]
.....	12 mono input [KP-120]
.....	16 mono input [KP-160]
Frequency Response .....	20Hz - 20KHz
T.H.D. ....	< 0.1% (1KHz full power)
Signal to Noise Ratio .....	-80dB
Input Sensitivity : Mic Input .....	-60dB
..... : Stereo Input .....	-40dB
..... : EFX Send .....	-20dB
..... : EFX Return .....	-20dB
Output .....	4V max
EQ : High .....	+/-15dB, 10KHz
..... : Mid .....	+/-15dB, 250Hz - 6KHz
..... : Low .....	+/-15dB, 60Hz
Power Requirement .....	AC 220V/50Hz



<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด  
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: [nts@nts-solution.com](mailto:nts@nts-solution.com)

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897