

PD-SERIES

PASSIVE PORTABLE LOUDSPEAKER



PASSIVE PORTABLE LOUDSPEAKER



TECHNICAL SPECIFICATION

PD-10 / PD-12 / PD-15 : PASSIVE PORTABLE LOUDSPEAKER

	PD-10	PD-12	PD-15
Frequency response	55Hz ~ 18KHz	45Hz ~ 18KHz	40Hz ~ 18KHz
Sensitivity [1w/1m]	94dB	96dB	98dB
RMS power handling	150W RMS	200W RMS	300W RMS
Voice coil	2" KSV	2.5" KSV	3" KSV
Magnet	40 Oz.	50 Oz.	60 Oz.
Low frequency	10" Woofer	12" Woofer	15" Woofer
High frequency	1.34" (34 mm.)	1.34" (34 mm.)	1.75" (44 mm.)
Nominal impedance	8Ω	8Ω	8Ω

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897

