


PMU-SERIES

POWER MIXER with DIGITAL EFFECT & USB INPUT



USB / SD CARD

MP3 INPUT



PMU-SERIES

Stereo Power Mixer with Digital Effect & USB Input

TECHNICAL SPECIFICATION

- 3 band EQ on all input
- 1 Aux send for external effects and monitoring
- Peak LED on all input
- PAD and PFL switch on all input
- Built in 16 program digital effect
- USB interface for MP3 input and playback
- 7 band graphic EQ

- PMU-601 : 6 Mono Input
- PMU-602 : 6 Mono + 2 Stereo Input
- PMU-801 : 8 Mono Input
- PMU-802 : 8 Mono + 2 Stereo Input
- PMU-1201 : 12 Mono Input

SPECIFICATION :	PMU-601 / PMU-602 / PMU-801 / PMU-802	PMU-1201
Power Output	150W x 2 @ 8Ω	180W x 2 @ 8Ω
.....	250W x 2 @ 4Ω	300W x 2 @ 4Ω
Frequency Response	20Hz - 20KHz	20Hz - 20KHz
T.H.D.	0.005% / 0.004% A-weighted	0.005% / 0.004% A-weighted
Signal to Noise Ratio	110dB / 112dB A-weighted	110dB / 112dB A-weighted
EQ : HIGH	+/-15dB, 12kHz	+/-15dB, 12kHz
: MID	+/-15dB, 100Hz - 8KHz	+/-15dB, 100Hz - 8KHz
: LOW	+/-15dB, 80Hz	+/-15dB, 80Hz

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoenakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897